

Elyte-T9 Electrolyte Analyzer

Available Models

- Elyte-T9A K⁺ / Na⁺
- Elyte-T9B K⁺ / Na⁺ / Cl⁻ / CO₂
- Elyte-T9C K⁺ / Na⁺ / Cl⁻ / Ca²⁺ / pH
- Elyte-T9D K⁺ / Na⁺ / Cl⁻ / Ca²⁺ / pH / CO₂
- Elyte-T9F K⁺ / Na⁺ / Cl⁻



SPECIFICATIONS

- Linux operating system, 800*480 color LCD touch screen.
- High performance electrodes; high precision and wide linearity range, with long shelf life (up to12 months for Na, K, Cl electrodes).
- Excellent, electrode shielding system, removing external interference and ensuring good stability.
- Real-time detection of each electrode working status, eliminating electrodes drift, ensuring accurate result.
- Possible to connect with a bar-code scanner, accidental power-off protection and automatic fault diagnosis function.
- Support high/low value calibrators and 3 levels of QC, automatic calibration of slope and intercept values, display of whole QC graphs.
- Environment friendly: paper-based material reagent pack.
- Two sampling modes: automatic sampling with auto sampler or manual sampling.
- Operational software can be upgraded through USB port.
- Automatic liquid level detection and alarms. Real-time diagnostic of system status and reagent pack status information.
- More than 100,000 test results can be stored with convenient sample results review.

O TECHNICAL INDEX

Parameter	CV%	Resolution	Range
K ⁺	≤ 1.0%	0.01mmol/L	0.50~15.00 mmol/L
Na⁺	≤ 1.0%	0.1mmol/L	30.0~200.0 mmol/L
Cl	≤ 1.0%	0.1mmol/L	30.0~200.0 mmol/L
Ca ²⁺	≤ 1.0%	0.01mmol/L	0.10~5.00 mmol/L
рН	≤ 1.0%	0.01mmol/L	4.0~9.50 (Unit)
CO ₂	≤ 1.0%	0.1mmol/L	6.0~50.0 mmol/L





Shenzhen Heto Medical Tech Co., Ltd.

Address: 4/F, Building No.4, Shenzhen Environmental Protection Industrial Park, No.31 Makan South Road, Nanshan District, Shenzhen, 518055, P.R.China.

Tel: +86 755-28935967 Fax: +86 755-28937587 Email: Sales@hetomedical.com

Web: www.hetomedical.com

